



IR 75 Front Cabin Automotive Window Films

Optical & Solar Properties

Performance results are calculated on 1/4" (6mm) clear glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards





IR 75 promises a more comfortable travel experience, imperceptibly delivering all-round UV block, reducing glare and limiting heat build-up.

IR 75 spectrally selective film for windshield^{*} and front windows effectively filters heat-transmitting radiation while retaining the visual clarity required by law. Delivering all-round UV block, and containing an Infra Red filtering nanoparticle formula that dramatically limits heat build-up, IR 75 ensures a more comfortable driver and passenger experience. Its subtle blue tint is virtually imperceptible to preserve the original appearance of the glazing.

Enhanced security with IR 75 Safe

IR 75 Safe delivers increased antifragmentation and break-in protection, together with exceptional heat and glare control.

Where lega

With SolarZone Automotive window films:

Feel Cool

SolarZone automotive films filter heat and glare for a more pleasant passenger experience and reduced air-conditioning load.

Look Cool

Choose from a variety of shades and light transmission levels to give your vehicle a custom appearance.

Protect Yourself

SolarZone works like sunscreen to protect your skin by rejecting 99% and over of harmful UV radiation.

Protect Your Car

Protect trim, upholstery, carpets and fittings from the heat, light and UV radiation that cause fading, so your car looks better longer and maintains its value.

Stay Safe

SolarZone films can help reduce the risk of injury from broken glass caused by projectiles, minor accidents or road debris. If security is a concern, check out SolarZone Safe automotive films; they make vehicle glass safer, and more resistant to crime.

Stay Private

Tinted films keep your possessions out of sight.

Stop Squinting

Cuts glare from the sun or from headlights to reduce eyestrain on long trips and in busy city traffic.

IR 75 - Optical & Solar Properties

	IR 75	IR 75 with 4 mil Safety
Item Number	R069IRM	R123IRM
Visible Light Transmitted %		76
Visible Light Reflected %		9
Ultra Violet Block %		99
Total Solar Energy Reflected %		7
Total Solar Energy Transmitted %		40
Total Solar Energy Absorbed %		53
Shading Coefficient		0.65
Total Solar Energy Rejected %		44



Performance results are calculated on 1/4" (6mm) clear glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards

US: T: 800-660-5559 | info@hanitatek.com | www.hanitatek.com Europe: T: +49 (0) 6142-2082 746 | info@hanita-europa.de | www.hanita-europa.de Australia: T: 1300-456-700 | info@hanitapacific.com.au | www.hanitapacific.com.au International: T: +972-4-985-9919 | solar@hanitacoatings.com | www.hanitacoatings.com



solar zone

